



OCEAN CRAFT
MARINE



OCM
YACHT TENDER 8.0M

VESSEL SPECIFICATIONS:

GENERAL SPECIFICATIONS:

- LOA: 7.84M
- Beam: 2.55M
- Tube Diameter 0.45M
- No. of Pax: 15 (According to CE category B)
- Classification Category "B," Offshore
- Weight (Empty Boat) 870 kg 1,918 lbs
- Weight (Full Average) 1800 kg 3,968 lbs
- Fuel Tank: Single fuel Tank of 93 Gallon

VESSEL FRP HULL:

- OCM Yacht Tender 8.0m RHIB "Turn-Key Ready" "V" shaped Laminated Fiberglass Reverse Chine Hull, Color: Off-white
- Anchor locker Forward
- 3 U-bolts (1 on bow, 2 on transom)
- S.S Heavy Duty Lifting Points (2 Foredeck & 2 Aft deck)

DECK/STRUCTURE:

- Single Futura Center Console, with forward seat w/small-form-factor smoked windscreen & grab-railing
- 2 x S.S Polished Pop-up mooring cleats on deck's aft section

PROPULSION:

- Single Mercury® 350HP Outboard Engines, XL 25" Shaft, with Electro-Hydraulic Power Steering Option, w/Black Color engine cowlings.
- Vessel View-502 5" Display w/Engine & Vessel Telemetry Integrated with Multifunction Displays, Fly-by-Wire DTS Control Binnacle, Tilt Helm wheel, and Installation, Stainless Steel Propeller, AGM - Optima Blue Top® Battery Banks, Tray, Selector Switches, etc

FUEL SYSTEM:

- Single Aluminum Fuel Tank (93 Gal. Total Onboard)
- Fuel shutoff valve, fuel & water-separator

TUBE SET:

- Tube Spec. Neoprene-Hypalon, Military-Grade Thickness, 1670 Dtex. Inflatable Tube-Set, Five (5) Compartmentalized w/ inflation and Over-pressure Valves, Color: Off-White
- Hypalon Patches on tube in Neptune grey color
- Hypalon soft grab handles 8 no.
- Rubber Handles 4 No.
- OCM Logos
- Double Fendering Rub-strake on tubes
- Hypalon Strip between fender strakes
- Diver Notch at port side of the Tube with cover

SEATING:

- OCM Custom Single Bolster Seat w/ Back Rest and Under seat Cooler Storage on-deck (Operator console)
- U-Bench Seat (for 4 to 5 PAX) with day bed insert
- Aft Athwartship Bench Seating with Back Rests

PROTECTION:

- Boat Cover
- Console Cover

ELECTRONICS/LIGHTING:

- LED Vessel Navigation & anchor Lights IAW COLREGS
- Automatic Electric Bilge Pumps (2) 500 GPH High Capacity, with Automatic Float Switch
- 12VDC Electric Distribution Bus/System with Breaker Panels & Battery Isolators
- AGM - Optima Blue Top® Battery Bank, Tray, Selector Switches and charging isolator (for accessory)